

MATERIAL SAFETY DATA SHEET

OMCO-EP-H

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME OMCO-EP-H

PRODUCT USE Lubricating Grease

MANUFACTURER Chemtool Incorporated
P.O. Box 538
8200 Ridgefield Road
Crystal Lake, IL 60039-0538 USA
Tel: (815) 459-1250
Fax: (815) 459-1955

SUPPLIER Oconomowoc Manufacturing Corp.
425 South Lapham Street
P.O. Box 426
Oconomowoc, WI 53066
Tel: (262) 567-8383
Fax: (262) 567-0389

EMERGENCY TELEPHONE Infotrac
U.S. and Canada - (800) 535-5053
Outside the U.S. and Canada - 001-352-323-3500

2. COMPOSITION, INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS No.	WEIGHT
CALCIUM COMPLEX THICKENER (PROPRIETARY INGREDIENT# 28287)	Proprietary	40-60 %
DISTILLATES, PETROLEUM, SOLVENT-REFINED HEAVY PARAFFINIC	64741-88-4	20-40 %
RESIDUAL OILS, PETROLEUM, REFINED (CAS NOS 64742-57-0, 64742-62-7 & 72623-83-7)	Mixture	7-13 %

COMPOSITION COMMENTS

Refer to section eight for exposure limits on ingredients.
Chemical ingredients not regulated by OSHA or SARA are treated confidentially.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

ACUTE EFFECTS

HEALTH HAZARDS, GENERAL

Not regarded as a health hazard under current legislation. Exposure to vapors generated at high temperatures may cause respiratory irritation.

CHRONIC EFFECTS

SENSITIZATION	No known information.
CARCINOGENICITY	IARC: Not listed as a Group 1, 2A, or 2B agent. OSHA: Not regulated. NTP: Not listed.

HEALTH WARNINGS

INHALATION. Heating can generate vapors that may cause respiratory irritation, nausea and headaches. Inhalation hazard at room temperature is unlikely due to the low volatility of this product. SKIN CONTACT. Repeated or prolonged contact can result in drying of the skin. EYE CONTACT. May cause slight eye irritation. May cause very slight transient (temporary) corneal injury. INGESTION. Can cause stomach ache and vomiting. Main hazard, if ingested, is aspiration into the lungs and subsequent pneumonitis.

OTHER INFORMATION

ROUTE OF ENTRY	Inhalation. Skin and/or eye contact. Ingestion.
MEDICAL SYMPTOMS	MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Not determined

4. FIRST AID MEASURES

INHALATION	Vapor inhalation under ambient conditions is normally not a problem. If overcome by vapor of hot product, immediately remove from source of exposure. Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. Get medical attention if any discomfort continues.
EYES	Rinse the eye with water immediately. Continue to rinse for at least 15 minutes. Contact physician if discomfort continues.
SKIN	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
INGESTION	DO NOT INDUCE VOMITING! Get medical attention immediately!

5. FIRE FIGHTING MEASURES

FLASH POINT (°C)	246 Cd OC (Cleveland open cup).
FLAMMABILITY LIMIT - LOWER(%)	N/D
FLAMMABILITY LIMIT - UPPER(%)	N/D
EXTINGUISHING MEDIA	Use: Carbon dioxide (CO ₂). Dry chemicals, sand, dolomite etc. Alcohol resistant foam. Water spray, fog or mist.
SPECIAL FIRE FIGHTING PROCEDURES	Use water to keep fire exposed containers cool and disperse vapors. Water spray may be used to flush spills away from exposures and dilute spills to non-flammable mixtures. Avoid water in straight hose stream; will scatter and spread fire. Keep run-off water out of sewers and water sources. Dike for water control.
UNUSUAL FIRE & EXPLOSION HAZARDS	Pressure will increase in over heated, closed containers.
HAZARDOUS COMBUSTION PRODUCTS	Acrid smoke/fumes. Oxides of: Carbon.
PROTECTIVE MEASURES IN CASE OF FIRE	Self-contained breathing equipment and chemical resistant clothing recommended.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS	Minimize skin contact.
PRECAUTIONS TO PROTECT THE ENVIRONMENT	Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with applicable government regulations.
SPILL CLEAN-UP PROCEDURES	Keep all sources of ignition and hot metal surfaces away from spill. Avoid contact with eyes or skin. Place leaking containers in well ventilated area. If fire potential exists, blanket spill with foam or use water spray to disperse vapors. Contain spill to minimize contaminated area and facilitate salvage or disposal. To clean up spill, flush area sparingly with water or use absorbant material. Avoid discharge to natural water ways.

7. HANDLING AND STORAGE

HANDLING PRECAUTIONS	Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Do not reuse container. Keep lid closed when not in use. Do not store or mix with strong oxidizers. Avoid spilling, skin and eye contact. Eye wash and emergency shower must be available at the work place.
STORAGE PRECAUTIONS	Store separate from strong acids and oxidizers. Keep away from heat, sparks and open flame.
STORAGE CRITERIA	Chemical storage.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

COMPONENT	STD	TWA	STEL	TWA	STEL
DISTILLATES, PETROLEUM, SOLVENT-REFINED HEAVY PARAFFINIC	OSHA			5 mg/m3 ^{**} (1)	
	ACGIH			5 mg/m3 ^{**} (1)	10 mg/m3 ^{**} (1)
RESIDUAL OILS, PETROLEUM, REFINED (CAS NOS 64742-57-0, 64742-62-7 & 72623-83-7)	OSHA			5 mg/m3 ^{**} (1)	
	ACGIH			5 mg/m3 ^{**} (1)	10 mg/m3 ^{**} (1)

INGREDIENT COMMENTS

^{**}(1) For respirable oil mist.

PROTECTIVE EQUIPMENT



ENGINEERING CONTROLS	Use engineering controls to reduce air contamination to permissible exposure level.
VENTILATION	No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.
RESPIRATORS	No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.
PROTECTIVE GLOVES	Chemical resistant gloves recommended to prevent prolonged or repeated contact.
EYE PROTECTION	Wear splash-proof eye goggles to prevent any possibility of eye contact.
PROTECTIVE CLOTHING	Wear appropriate clothing to prevent repeated or prolonged skin contact.
HYGIENIC WORK PRACTICES	Wash at the end of each work shift and before eating, smoking and using the toilet.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/PHYSICAL STATE	Grease.		
COLOR	Tan.		
ODOR	Mild (or faint). Petroleum.		
SOLUBILITY DESCRIPTION	Insoluble in water.		
DENSITY	0.96	Temperature (°C)	16
VAPOR DENSITY (air=1)	> 5		
VAPOR PRESSURE	< 0.01 mmHg	Temperature (°C)	20
EVAPORATION RATE	< 1	Reference	BuAc=1
pH-VALUE, CONC. SOLUTION	N/A		

10. STABILITY AND REACTIVITY

STABILITY	Normally stable.
CONDITIONS TO AVOID	Avoid contact with acids and oxidizing substances.
HAZARDOUS POLYMERIZATION	Will not occur.
POLYMERIZATION DESCRIPTION	Not applicable
HAZARDOUS DECOMPOSITION PRODUCTS	Oxides of: Carbon.

11. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION	No experimental toxicological data on the preparation as such is available.
----------------------------------	---

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION There is no ecological data on the product itself.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS Spilled material, unused contents and empty containers must be disposed of in accordance with local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT HAZARD CLASS Not regulated.

SEA TRANSPORT NOTES Not regulated.

AIR TRANSPORT NOTES Not regulated.

15. REGULATORY INFORMATION

US FEDERAL REGULATIONS

COMPONENT	SARA 302	CERCLA	SARA 313
CALCIUM COMPLEX THICKENER (PROPRIETARY INGREDIENT# 28287)	No	No	No
DISTILLATES, PETROLEUM, SOLVENT-REFINED HEAVY PARAFFINIC	No	No	No
RESIDUAL OILS, PETROLEUM, REFINED (CAS NOS 64742-57-0, 64742-62-7 & 72623-83-7)	No	No	No

CLEAN AIR ACT

SARA(311/312) HAZARD CATEGORIES None

US STATE REGULATIONS

STATE REGULATORY STATUS PROPOSITION 65: This product may contain the following chemical(s) considered by the State of California's Safe Drinking Water and Toxic Enforcement Act of 1986 as causing cancer or reproductive toxicity, and for which warnings are now required:
1-Naphthylamine, CAS # 134-32-7, <1ppm
2-Naphthylamine, CAS # 91-59-8, <1ppm

REGULATORY STATUS (Canada) Not a controlled product.

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM - WHMIS

INVENTORIES

COMPONENT	CAN	US	EU	AUS	JAP	KOR	CHN	PHLP
RESIDUAL OILS, PETROLEUM, REFINED (CAS NOS 64742-57-0, 64742-62-7 & 72623-83-7)	DSL	Yes	EINECS	Yes	Yes	Yes		Yes
DISTILLATES, PETROLEUM, SOLVENT-REFINED HEAVY PARAFFINIC	DSL	Yes	EINECS	Yes	Yes	Yes	Yes	
CALCIUM COMPLEX THICKENER (PROPRIETARY INGREDIENT# 28287)	DSL	Yes	EINECS					

16. OTHER INFORMATION

HEALTH	Irritation, minor residual injury (1) - HMIS/NFPA
FLAMMABILITY	Burns only if pre-heated (1) - HMIS/NFPA
REACTIVITY	Normally Stable (0) - HMIS/NFPA
REVISION COMMENTS	Section 1: Name Change Section 2: Ingredients Revised by James W. Hermann
PREPARED BY	John Dingess
REVISION No.	1
REVISION No./Repl. MSDS of	0
DATE	October 10, 2003
PRINTING DATE:	2004-08-30
DISCLAIMER	While the information and recommendations set forth herein are believed to be accurate as of the date thereof, Chemtool Incorporated makes no warranty with respect thereto and disclaims all liability from reliance therein.